Safety Data Sheet (SDS)

Effective Date: June 1, 2016

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

Material Name STANDARD LIQUID FOR CALIBRATING VISCOMETERS JS 100

Recommended Use Standard liquids for calibrating viscometer.

Restricted Use Other than those above. Manufacturer/Supplier : Nippon Grease Co., Ltd.

1-12-4, Suehiro-cho, Tsurumi-ku, Yokohama, 230-0045, Japan

FAX.+81-45-504-2213

Telephone/Fax : Sales Planning Division TEL.+81-45-501-0781

Emergency Telephone: Technical Research Laboratory TEL.+81-78-731-8147

Number

SDS Code : E478900600

2. HAZARDS IDENTIFICATION

GHS Classification : NOT HAZARDOUS

GHS Label Elements

Symbol(s) : No symbol **Signal Words** : No signal word

: Not classified under GHS criteria. **Hazard Statement**

GHS Precautionary Statements

: No precautionary phrases. Prevention Response : No precautionary phrases. : No precautionary phrases. Storage Disposal No precautionary phrases.

Unclassified Hazard : Please see Section 4 - 8 before use for Prevention/Response/Storage/Disposal.

Used oil may contain harmful impurities. Information

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance or Mixture Mixture

Chemical Description Standard liquids for calibrating viscometer.

Component Information : Base oil 100% **Chemical Formula** : Not possible to define.

CAS registry number : 8042-47-5

Additional Information : If product contained highly refined mineral oil, it contains <3% DMSO-extract,

according to IP346.

Pollutant Release and Transfer : Not applicable

Register (PRTR) Law

Industrial Safety and Health

Law **Poisonous and Deleterious** : Not applicable : Not applicable

Substance Control Law

The specific chemical identities and percentages of composition have been withheld as trade secrets.

4. FIRST AID MEASURES

General Information

: Not expected to be a health hazard when used under normal conditions.

Inhalation : Remove casualty to fresh air and keep at rest in a position comfortable for breathing. Cover with blanket to keep warm and rest in a quiet surrounding. Seek immediate

medical advice and attention.

Skin Contact : Wash skin with large amount of water using soap.

Eye Contact : Rinse cautiously with clean water for several minutes. Remove contact lenses, if present and easy to do, and continue rinsing. After rinsing for a minimum of 15

minutes, seek medical advice and attention.

Ingestion : Without inducing vomiting, call a doctor for treatment. If mouth has been dirtied, clean

with water.

Most Important Symptoms/Effects, Acute

: If swallowed, may irritate mucous membrane of stomach and induce vomiting. Inhalation if mist may cause feeling ill. Skin contact and eye contact may cause

& Delayed irritation.

Immediate Medical Attention, Special

: Treat symptomatically. Call a doctor or poison control center for guidance.

Treatment

5. FIRE FIGHTING MEASURES

Clear fire area of all non-emergency personnel.

Suitable Extinguishing

Media

: Concentrated strong liquid in mist and powder forms, carbon dioxide and foam. Use powder and carbon dioxide may be used small fires only. Effective to use foam to

shutdown the air in a large fires.

Unsuitable Extinguishing

Media

: Do not use water in a jet.

Specific Hazards Arising from Chemicals

: Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds

Fire fighting instructions

: Water the surrounding equipment to cool them down. Cordon off the affected place and its vicinity to all, except the concerned parties.

Protective Equipment & Precautions for Fighters : Ensure to wear protective equipment and approach from windward.

6. ACCIDENTAL RELEASE MEASURES

Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Section 8 of this SDS. See Section 13 for information on disposal. Observe the relevant local and international regulations.

Personal Precautions, Protective Equipment and Emergency Procedures

: Avoid contact with skin and eyes. Prepare suitable equipment and materials.

Environmental **Precautions**

: Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. In event of entering in the sea, extend oil fences to prevent from spreading, and sop up with absorbent materials. Use chemicals and/or detergents, they must satisfy technical standards as set by the Ministry of Land, Infrastructure and Transport / Ministry of the Environment.

Methods and Material for Containment and Clean Up

: Promptly remove all ignition sources and stop leakages. In a small leakage, absorb and recover by use of soil, sand, sawdust and waste clothes. In a large leakage, cordon off the danger zone, prevent from entering and enclose it with sand bank and stop outflow. Cover liquid surface with foam, and recover liquid into containers.

: Local authorities should be advised if significant spillages cannot be contained.

7. HANDLING AND STORAGE

Technical Measures

HANDLING

Additional Advice

: In handling this material over the allocated volume, ensure approval to meet requires of

the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take measures against static discharge. Ensure to wear clothing and shoes made of conductive materials. When fixing or processing machine, it carries out after removing dangerous objects completely. NEVER suck up (siphoning) this material by mouth. Wear suitable protect equipment if skin or eye contact may cause. Seal containers hermetically without handling in violent such as falling, dropping, or jolting.

see Section 8

Ventilation Precautions **Precautions for Safe**

Handling

STRAGE Conditions for Safe

Storage

Technical Measures Precautions for Safe Stroage

Recommended Materials

Use under normal temperature. Prevent from mixing water and impurity. Avoid contact with halogens, strong acids, alkali and oxidizing materials.

: Keep containers tightly closed and in a cool, well-ventilated place away from direct sunlight. It is recommended to lock up storage area. Use properly labelled and closeable containers. Avoid heat, sparks, open flame and static accumulation.

: All electrical appliances shall be explosion-proof types, and they all must be earthed. : Avoid contact and storage in same place with halogens, strong acids, alkali and oxidizing materials.

: Storage in original containers. Do not pressurize empty containers. May cause rupture. Do not weld, heat up, drill or cut containers. May ignite the residue and cause explosion.

: Seal or install ventilations for mist occurs. Install eye shower and body shower near

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

If the American Conference of Governmental Industrial Hygienists (ACGIH) value is provided on this document, it is provided for information only.

working site. : Not specified

Standard Concentration Control

Equipment

OSHA, Permissible **Exposure Limits (PEL) Occupational Exposure**

Limits **Protective Equipment Respiratory Protection** : 5mg/m³ (as Oil mist, mineral)

: Japan Society for Occupational Health(2012)⁽¹⁾ 3mg/m³ (as Oil mist, mineral) 5mg/m³ (as Oil mist, mineral) ACGIH(2012) TWA[Inhalable fraction.](2) : Skin protection not ordinarily required beyond standard issue work clothes.

: No respiratory protection is ordinarily required under normal conditions of use. Use appropriate equipment in response to the circumstances.

Hand Protection Eve Protection Skin and Body **Protection**

: Use oil-proof protective hand gloves under prolonged or repeated skin contact. : Wear safety glasses or full face shield if splashes are likely to occur.

: Use oil-proof/long sleeved clothing under prolonged usage.

Appropriate Sanitary : Remove immediately all contaminated clothing. Contaminated clothing must be Measures: laundered before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : Liquid. Colour : Clear.

Odour Slightly odour. **Odour threshold** Data not available. Hq Not applicable.

Kinetic Viscosity 100.8mm²/s (20°C) Flash point 194°C (COC) Flammability of the product Flammable.

Typical 1 - 7 %(V) (estimated) **Upper / lower Flammability or Explosion limits**

Auto-ignition temperature Data not available.

Density Approx. 0.86g/cm³ (15°C) Solubility Water: Negligible.

Decomposition Temperature Data not available. Vapour pressure Data not available. Vapour density Data not available. n-octanol/water partition coefficient (log Pow) Data not available.

Evaporation rate Data not available.

10. STABILITY AND REACTIVITY

Chemical Stability : Stable under normal condition.

Hazardous Reactivity : Avoid contact with strong oxidizing agent.

Conditions to Avoid : Avoid contact with halogens, strong acids, alkalis, and oxidizing materials.

Incompatible Materials : Data not available.

Hazardous Decomposition: Hazardous decomposition products are not expected to form during normal storage.

Generates smoke, carbon monoxide, sulfurous acid gas etc. during combustion. **Products**

11. TOXICOLOGICAL INFORMATION

Basis for Assessment Information given is based on data on the components and the toxicology of similar

products. Unless indicated otherwise, the data presented is representative of the main

component of a whole product, rather than for individual component(s).

Expected low toxicity: LD₅₀ > 5000 mg/kg(estimated)⁽³⁾ 1 Oral **Acute Toxicity**

2 Dermal Expected low toxicity: LD₅₀ > 5000 mg/kg(estimated)⁽³⁾

3 Inhalation(Vapour) Data not available

4 Inhalation(Mist) Expected low toxicity: $LC_{50} > 5 \text{ mg/l}$, 4h (estimated) (3)

Skin Corrosion/Irritation : Expected not classified as a skin irritation. (3) Prolonged/repeated contact may cause

defatting of the skin which can lead to dermatitis. : Expected not classified as an eye irritation. (3) Capable of slightly irritating.

Damage/Irritation

Respiratory or Skin

: No data available concerning respiratory sensitisation.

Not expected to be a skin sensitiser. (3) Sensitisation

Germ Cell Mutagenicity Not considered a mutagenic hazard. (3) Carcinogenicity : Components are not known to be associated with carcinogenic effects. (3)

: Not expected to be a hazard. (3) Reproductive and

Developmental Toxicity

Specific target organ : Not expected to be a hazard. (3)

toxicity

Serious Eye

12. ECOLOGICAL INFORMATION

Basis for Assessment Ecotoxicological data have not been determined specifically for this product.

> Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the

main component of a whole product, rather than for individual component(s).

Caution : Poorly soluble mixture. May cause physical fouling of aquatic organisms.

Toxicity : Expected to be of low toxicity: Practically non toxic: LC/LL/EL/IL50

Mobility : Generally floats on water.

> : Lubricating oil components have estimated log Koc >3, indicating these components are likely to be adsorbed onto soil and sediment and are not likely to leach to ground

water.

Persistence/degradability : Expected to be not readily biodegradable. Major constituents are expected to be

inherently biodegradable.

Bioaccumulative Potential : Not expected to be a hazard. It may contains components with the potential to

bioaccumulate. (3)

Not classified because this product not contained substances listed on Montreal Hazardous to ozone layer

Protocol and Ozone Layer Protection Law.

13. DISPOSAL CONSIDERATIONS

Material Disposal

- 1 Waste disposal yourself or entrust the industrial waste treatment company who obtained the prefectural governor's permission or municipal corporation. Disposal should be in accordance with applicable regional, national, and local laws and regulations.
- 2 Do not dispose into the environment, in drains or in water courses.
- 3 For landfill disposal, destroy by fire and confirm cinders agreed to Waste Disposal Law.
- 4 In event of burning this material, ensure to carryout work in safe place with guards in position, and select a method that would not cause any harm or damage to others

during combustion or explosion.

Container Disposal

: Purify and recycle or performs suitable disposal in accordance with the standard of related laws and regulations. Disposal with remove content completely.

14. TRANSPORT INFORMATION

International Restriction

UN Class, Shipping

: Not Dangerous Goods.

Name

UN Number : Not applicable.

Marine Pollutant Yes.

Domestic Restriction Since domestic laws and regulations shown below are applicable, containers and

transportation methods shall be required to follow each and every regulation.

Land Fire Service Law: Dangerous goods. Group 4 (flammable liquid), Class 3 petroleum, Danger grade III If product classified as dangerous goods, use containers (other than tanker, tank car Container:

and tank truck) for transportation usage, shall meet the Clause 2, Notice Attachment 3,

concerning dangerous materials.

Sea Ship Safety Law: Not Dangerous Goods. Civil Aeronautics Act: Not Dangerous Goods. Air

Specific safety measures and conditions for

transportation

1 Caution: Flammable.

2 Transport remarkably with containers may not cause friction or agitation.

3 Display signage on vehicle and provide with fire fighting equipment, if and when required to transport more than the specified quantity. Total piled height of vehicle shall

be less than 3 meters.

4 Consolidation of this material with dangerous goods belonging to the 1st and 6th

Classification is prohibited.

5 Abide by other laws and regulations that are applicable.

15. REGULATORY INFORMATION

Fire Service Law : Dangerous goods. Group 4 (flammable liquid), Class 3 petroleum, Danger grade

Pollutant Release and Transfer Register (PRTR) : Not applicable

Industrial Safety and Health : Not applicable

Poisonous and Deleterious **Substance Control Law**

: Not applicable

Marine Pollution Protection

: Waste Oil Regulation.

Law

Sewage Control Law : Mineral Oil Disposal Regulation. (5mg/L)

Water Pollution Prevention

: Oil Disposal Regulation. (5mg/L)

Law

Waste Disposal and Public

: Industrial Waste Regulation.

Cleaning Law

16. OTHER INFORMATION

- Subscribe "%" in this document means weight percentage.

- 1. Recommendation of Occupational Exposure Limits (2012), Japanese Society of Occupational Health
- 2. Thresholds limit values for chemical substances and physical agents and biological exposure indices, ACGIH (2012)
- 3. SDS of EU suppliers (2010-2012)

[Reference]

- Globally Harmonized System of Classification and Labelling of Chemicals (GHS) 4th revised edition, UNITED NATIONS(2011)
- Japanese Standards Association (JSA), JIS Z 7253:2012, JIS Z 7252:2014
- National Institute of Technology and Evaluation (nite), "GHS Information"
- Ministry of Economy, Trade and Industry, Chemical Management site.
- Ministry of Health, Labour and Welfare, "Label and MSDS information for GHS model"

Safety Data Sheet (SDS) about hazardous chemical is provided for a entrepreneur as reference information for safety handling. Refer to this document and perform suitable handling. Nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use. There is no warranty against intellectual property infringement. The information contained in this document is based upon data believed to be reliable through our supply chain at the time. So, we could not

Nippon Grease Co., Ltd. E4789006 Date: June 1, 2016 Page: 5/5

guarantee all about the contents. This document is based on JIS Z7253:2012, and is not a guarantee of safety. Contents of SDS updated periodically. SDS compliance is required as a rule to all business enterprises engaged in transaction of chemicals (including products containing them) with other businesses. Retailer/ Wholesaler must provide newest SDS to customers.