Safety Data Sheet (SDS)

		Effec	tive Date: November 1, 2021
1. IDENTIFICATION OF TH	E SUBSTANCE/MIXTURE AND C	OF THE COMPANY/UN	DERTAKING
Material Name	: STANDARD LIQUID FOR CALIB	RATING VISCOMETERS	S JS 100
Recommended Use	: Standard liquids for calibrating vis	scometer.	
Restricted Use	: Other than those above.		
Manufacturer/Supplier	: Nippon Grease Co., Ltd.		
	1-12-4, Suehiro-cho, Tsurumi-ku,	Yokohama, 230-0045, Ja	apan
Telephone/Fax	: Sales Management Division	TEL.+81-45-501-0781	FAX.+81-45-504-2217
Emergency Telephone	: Technical Research Laboratory	TEL.+81-78-731-8147	
Number			
SDS Code	: E478900600		

2. HAZARDS IDENTIFI	CATION
GHS Classification	: NOT HAZARDOUS
GHS Label Elements	
Symbol(s)	: No symbol
Signal Words	: No signal word
Hazard Statement	: Not classified under GHS criteria.
GHS Precautionary S	tatements
Prevention	: No precautionary phrases.
Response	: No precautionary phrases.
Storage	: No precautionary phrases.
Disposal	: No precautionary phrases.
Unclassified Hazard	: Please see Section 4 - 8 before use for Prevention/Response/Storage/Disposal.
Information	Used oil may contain harmful impurities.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance or Mixture	: Mixture
Chemical Description	: Standard liquids for calibrating viscometer.
Component Information	: Base oil 100%
Chemical Formula	: Not possible to define.
CAS registry number	: 8042-47-5
Additional Information	: If product contained highly refined mineral oil, it contains <3% DMSO-extract, according to IP346.
Pollutant Release and Transfer	: Not applicable
Register (PRTR) Law	
Industrial Safety and Health Law	: Not applicable
Poisonous and Deleterious	: Not applicable
Substance Control Law	
The energific chemical identities or	d percentages of composition have been withhold as trade secrets

The specific chemical identities and percentages of composition have been withheld as trade secrets.

4. FIRST AID MEASURES	
General Information	: Not expected to be a health hazard when used under normal conditions.
Inhalation	 Remove casualty to fresh air and keep at rest in a position comfortable for breathing. Cover with blanket to keep warm and rest in a quiet surrounding. Seek immediate medical advice and attention.
Skin Contact	: Wash skin with large amount of water using soap.
Eye Contact	 Rinse cautiously with clean water for several minutes. Remove contact lenses, if present and easy to do, and continue rinsing. After rinsing for a minimum of 15 minutes, seek medical advice and attention.
Ingestion	: Without inducing vomiting, call a doctor for treatment. If mouth has been dirtied, clean with water.
Most Important	: If swallowed, may irritate mucous membrane of stomach and induce vomiting.
Symptoms/Effects, Acute & Delayed	Inhalation if mist may cause feeling ill. Skin contact and eye contact may cause irritation.
Immediate Medical Attention, Special Treatment	: Treat symptomatically. Call a doctor or poison control center for guidance.

5. FIRE FIGHTING MEASURES

Clear fire area of all non-em	ergency personnel.
Suitable Extinguishing	: Concentrated strong liquid in mist and powder forms, carbon dioxide and foam. Use
Media	powder and carbon dioxide may be used small fires only. Effective to use foam to shutdown the air in a large fires.
Unsuitable Extinguishing Media	: Do not use water in a jet.

Specific Hazards Arising from Chemicals	: Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds
Fire fighting instructions	 Water the surrounding equipment to cool them down. Cordon off the affected place and its vicinity to all, except the concerned parties.
Protective Equipment & Precautions for Fighters	: Ensure to wear protective equipment and approach from windward.

Nippon Grease Co., Ltd. E4789006 Date: November 1, 2021 Page:2/5

6. ACCIDENTAL RELEASE MEASURES

6. ACCIDENTAL RELEASE			
Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see			
Section 8 of this SDS. See Section 13 for information on disposal. Observe the relevant local and international			
regulations.			
Personal Precautions,	: Avoid contact with skin and eyes. Prepare suitable equipment and materials.		
Protective Equipment and			
Emergency Procedures			
Environmental	: Use appropriate containment to avoid environmental contamination. Prevent from		
Precautions	spreading or entering drains, ditches or rivers by using sand, earth, or other		
	appropriate barriers. In event of entering in the sea, extend oil fences to prevent from		
	spreading, and sop up with absorbent materials. Use chemicals and/or detergents,		
	they must satisfy technical standards as set by the Ministry of Land, Infrastructure and		
	Transport / Ministry of the Environment.		
Methods and Material for	: Promptly remove all ignition sources and stop leakages. In a small leakage, absorb		
Containment and Clean	and recover by use of soil, sand, sawdust and waste clothes. In a large leakage,		
Up	cordon off the danger zone, prevent from entering and enclose it with sand bank and		
00	stop outflow. Cover liquid surface with foam, and recover liquid into containers.		
Additional Advice	: Local authorities should be advised if significant spillages cannot be contained.		
Additional Advice	. Local automies should be advised it significant spinages cannot be contained.		
7. HANDLING AND STORA	GE		
HANDLING			
_	. In bandling this material over the allocated volume, ensure approval to meet requires		
Technical Measures	: In handling this material over the allocated volume, ensure approval to meet requires of the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take		
_	of the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take measures against static discharge. Ensure to wear clothing and shoes made of		
_	of the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take measures against static discharge. Ensure to wear clothing and shoes made of conductive materials. When fixing or processing machine, it carries out after removing		
_	of the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take measures against static discharge. Ensure to wear clothing and shoes made of		
_	of the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take measures against static discharge. Ensure to wear clothing and shoes made of conductive materials. When fixing or processing machine, it carries out after removing		
_	of the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take measures against static discharge. Ensure to wear clothing and shoes made of conductive materials. When fixing or processing machine, it carries out after removing dangerous objects completely. NEVER suck up (siphoning) this material by mouth.		
_	of the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take measures against static discharge. Ensure to wear clothing and shoes made of conductive materials. When fixing or processing machine, it carries out after removing dangerous objects completely. NEVER suck up (siphoning) this material by mouth. Wear suitable protect equipment if skin or eye contact may cause. Seal containers		
Technical Measures	of the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take measures against static discharge. Ensure to wear clothing and shoes made of conductive materials. When fixing or processing machine, it carries out after removing dangerous objects completely. NEVER suck up (siphoning) this material by mouth. Wear suitable protect equipment if skin or eye contact may cause. Seal containers hermetically without handling in violent such as falling, dropping, or jolting.		
Technical Measures Ventilation Precautions Precautions for Safe	 of the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take measures against static discharge. Ensure to wear clothing and shoes made of conductive materials. When fixing or processing machine, it carries out after removing dangerous objects completely. NEVER suck up (siphoning) this material by mouth. Wear suitable protect equipment if skin or eye contact may cause. Seal containers hermetically without handling in violent such as falling, dropping, or jolting. see Section 8 		
Technical Measures	 of the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take measures against static discharge. Ensure to wear clothing and shoes made of conductive materials. When fixing or processing machine, it carries out after removing dangerous objects completely. NEVER suck up (siphoning) this material by mouth. Wear suitable protect equipment if skin or eye contact may cause. Seal containers hermetically without handling in violent such as falling, dropping, or jolting. see Section 8 Use under normal temperature. Prevent from mixing water and impurity. Avoid contact 		
Technical Measures Ventilation Precautions Precautions for Safe Handling	 of the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take measures against static discharge. Ensure to wear clothing and shoes made of conductive materials. When fixing or processing machine, it carries out after removing dangerous objects completely. NEVER suck up (siphoning) this material by mouth. Wear suitable protect equipment if skin or eye contact may cause. Seal containers hermetically without handling in violent such as falling, dropping, or jolting. see Section 8 Use under normal temperature. Prevent from mixing water and impurity. Avoid contact with halogens, strong acids, alkali and oxidizing materials. 		
Technical Measures Ventilation Precautions Precautions for Safe Handling STRAGE Conditions for Safe	 of the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take measures against static discharge. Ensure to wear clothing and shoes made of conductive materials. When fixing or processing machine, it carries out after removing dangerous objects completely. NEVER suck up (siphoning) this material by mouth. Wear suitable protect equipment if skin or eye contact may cause. Seal containers hermetically without handling in violent such as falling, dropping, or jolting. see Section 8 Use under normal temperature. Prevent from mixing water and impurity. Avoid contact with halogens, strong acids, alkali and oxidizing materials. Keep containers tightly closed and in a cool, well-ventilated place away from direct 		
Technical Measures Ventilation Precautions Precautions for Safe Handling STRAGE	 of the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take measures against static discharge. Ensure to wear clothing and shoes made of conductive materials. When fixing or processing machine, it carries out after removing dangerous objects completely. NEVER suck up (siphoning) this material by mouth. Wear suitable protect equipment if skin or eye contact may cause. Seal containers hermetically without handling in violent such as falling, dropping, or jolting. see Section 8 Use under normal temperature. Prevent from mixing water and impurity. Avoid contact with halogens, strong acids, alkali and oxidizing materials. Keep containers tightly closed and in a cool, well-ventilated place away from direct sunlight. It is recommended to lock up storage area. Use properly labelled and 		
Technical Measures Ventilation Precautions Precautions for Safe Handling STRAGE Conditions for Safe	 of the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take measures against static discharge. Ensure to wear clothing and shoes made of conductive materials. When fixing or processing machine, it carries out after removing dangerous objects completely. NEVER suck up (siphoning) this material by mouth. Wear suitable protect equipment if skin or eye contact may cause. Seal containers hermetically without handling in violent such as falling, dropping, or jolting. see Section 8 Use under normal temperature. Prevent from mixing water and impurity. Avoid contact with halogens, strong acids, alkali and oxidizing materials. Keep containers tightly closed and in a cool, well-ventilated place away from direct sunlight. It is recommended to lock up storage area. Use properly labelled and closeable containers. Avoid heat, sparks, open flame and static accumulation. 		
Technical Measures Ventilation Precautions Precautions for Safe Handling STRAGE Conditions for Safe Storage Technical Measures	 of the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take measures against static discharge. Ensure to wear clothing and shoes made of conductive materials. When fixing or processing machine, it carries out after removing dangerous objects completely. NEVER suck up (siphoning) this material by mouth. Wear suitable protect equipment if skin or eye contact may cause. Seal containers hermetically without handling in violent such as falling, dropping, or jolting. see Section 8 Use under normal temperature. Prevent from mixing water and impurity. Avoid contact with halogens, strong acids, alkali and oxidizing materials. Keep containers tightly closed and in a cool, well-ventilated place away from direct sunlight. It is recommended to lock up storage area. Use properly labelled and closeable containers. Avoid heat, sparks, open flame and static accumulation. All electrical appliances shall be explosion-proof types, and they all must be earthed. 		
Technical Measures Ventilation Precautions Precautions for Safe Handling STRAGE Conditions for Safe Storage Technical Measures Precautions for Safe	 of the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take measures against static discharge. Ensure to wear clothing and shoes made of conductive materials. When fixing or processing machine, it carries out after removing dangerous objects completely. NEVER suck up (siphoning) this material by mouth. Wear suitable protect equipment if skin or eye contact may cause. Seal containers hermetically without handling in violent such as falling, dropping, or jolting. see Section 8 Use under normal temperature. Prevent from mixing water and impurity. Avoid contact with halogens, strong acids, alkali and oxidizing materials. Keep containers tightly closed and in a cool, well-ventilated place away from direct sunlight. It is recommended to lock up storage area. Use properly labelled and closeable containers. Avoid heat, sparks, open flame and static accumulation. All electrical appliances shall be explosion-proof types, and they all must be earthed. Avoid contact and storage in same place with halogens, strong acids, alkali and 		
Technical Measures Ventilation Precautions Precautions for Safe Handling STRAGE Conditions for Safe Storage Technical Measures Precautions for Safe Stroage	 of the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take measures against static discharge. Ensure to wear clothing and shoes made of conductive materials. When fixing or processing machine, it carries out after removing dangerous objects completely. NEVER suck up (siphoning) this material by mouth. Wear suitable protect equipment if skin or eye contact may cause. Seal containers hermetically without handling in violent such as falling, dropping, or jolting. see Section 8 Use under normal temperature. Prevent from mixing water and impurity. Avoid contact with halogens, strong acids, alkali and oxidizing materials. Keep containers tightly closed and in a cool, well-ventilated place away from direct sunlight. It is recommended to lock up storage area. Use properly labelled and closeable containers. Avoid heat, sparks, open flame and static accumulation. All electrical appliances shall be explosion-proof types, and they all must be earthed. Avoid contact and storage in same place with halogens, strong acids, alkali and oxidizing materials. 		
Technical Measures Ventilation Precautions Precautions for Safe Handling STRAGE Conditions for Safe Storage Technical Measures Precautions for Safe Stroage Recommended	 of the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take measures against static discharge. Ensure to wear clothing and shoes made of conductive materials. When fixing or processing machine, it carries out after removing dangerous objects completely. NEVER suck up (siphoning) this material by mouth. Wear suitable protect equipment if skin or eye contact may cause. Seal containers hermetically without handling in violent such as falling, dropping, or jolting. see Section 8 Use under normal temperature. Prevent from mixing water and impurity. Avoid contact with halogens, strong acids, alkali and oxidizing materials. Keep containers tightly closed and in a cool, well-ventilated place away from direct sunlight. It is recommended to lock up storage area. Use properly labelled and closeable containers. Avoid heat, sparks, open flame and static accumulation. All electrical appliances shall be explosion-proof types, and they all must be earthed. Avoid contact and storage in same place with halogens, strong acids, alkali and oxidizing materials. Storage in original containers. Do not pressurize empty containers. May cause 		
Technical Measures Ventilation Precautions Precautions for Safe Handling STRAGE Conditions for Safe Storage Technical Measures Precautions for Safe Stroage	 of the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take measures against static discharge. Ensure to wear clothing and shoes made of conductive materials. When fixing or processing machine, it carries out after removing dangerous objects completely. NEVER suck up (siphoning) this material by mouth. Wear suitable protect equipment if skin or eye contact may cause. Seal containers hermetically without handling in violent such as falling, dropping, or jolting. see Section 8 Use under normal temperature. Prevent from mixing water and impurity. Avoid contact with halogens, strong acids, alkali and oxidizing materials. Keep containers tightly closed and in a cool, well-ventilated place away from direct sunlight. It is recommended to lock up storage area. Use properly labelled and closeable containers. Avoid heat, sparks, open flame and static accumulation. All electrical appliances shall be explosion-proof types, and they all must be earthed. Avoid contact and storage in same place with halogens, strong acids, alkali and oxidizing materials. 		

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

If the American Conference of Governmental Industrial Hygienists (ACGIH) value is provided on this document, it is provided for information only. **Equipment** : Seal or install ventilations for mist occurs. Install eye shower and body shower near

Equipment	working site.
Standard Concentration	: Not specified
Control	
OSHA, Permissible	: 5mg/m³ (as Oil mist, mineral)
Exposure Limits (PEL)	
Occupational Exposure	: Japan Society for Occupational Health(2018) ⁽¹⁾ 3mg/m ³ (as Oil mist, mineral)
Limits	ACGIH(2012) TWA[Inhalable fraction.] ⁽²⁾ 5mg/m ³ (as Oil mist, mineral)
Protective Equipment	: Skin protection not ordinarily required beyond standard issue work clothes.
Respiratory Protection	: No respiratory protection is ordinarily required under normal conditions of use. Use
, , ,	appropriate equipment in response to the circumstances.
Hand Protection	: Use oil-proof protective hand gloves under prolonged or repeated skin contact.
Eye/Face Protection	: Wear safety glasses or full face shield if splashes are likely to occur.
Skin and Body	: Use oil-proof/long sleeved clothing under prolonged usage.
Protection	· · · · · · · · · · · · · · · · · · ·

Appropriate Sanitary	: Remove immediately all contaminated clothing. Contaminated clothing must be
Measures:	laundered before reuse.

9. PHYSICAL AND CHEMIC	AL PROPERTIES	
Physical state		: Liquid.
Colour		: Clear.
Odour		: Slightly odour.
рН		: Not applicable.
Melting point/Freezing poir	nt	: Data not available.
Boiling point or Initial boili		: Data not available.
range		
Flash point		: 194°C (COC)
Evaporation rate		: Data not available.
Flammability		: Capable of catching fire.
Upper / lower Flammability	or Explosion limits	1 0
	or Explosion mints	: Typical 1 - 7 %(V) (estimated) : Data not available.
Vapour pressure		
Density Solubility		: Approx. 0.86g/cm ³ (15°C)
Solubility	n a l <i>hu</i> atan	: Water: Negligible.
Partition coefficient n-octa	noi/water	: Data not available.
Auto-ignition temperature		: Data not available.
Decomposition temperatur	e	: Data not available.
Kinetic viscosity		: 100.8mm²/s (20°C)
Relative vapour density		: Data not available.
Particle characteristics		: Data not available.
10. STABILITY AND REACT		
Chemical Stability	: Stable under normal	
Hazardous Reactivity	: Avoid contact with st	rong oxidizing agent.
Conditions to Avoid	: Avoid contact with ha	alogens, strong acids, alkalis, and oxidizing materials.
Incompatible Materials	: Data not available.	
Hazardous Decomposition	: Hazardous decompo	sition products are not expected to form during normal storage.
Products		arbon monoxide, sulfurous acid gas etc. during combustion.
11. TOXICOLOGICAL INFO	RMATION	
Basis for Assessment	Information given is ba	sed on data on the components and the toxicology of similar
		ated otherwise, the data presented is representative of the main
		product, rather than for individual component(s).
Acute Toxicity		Expected low toxicity: $LD_{50} > 5000 \text{ mg/kg}(\text{estimated})^{(3)}$
		Expected low toxicity: $LD_{50} > 5000 \text{ mg/kg}(\text{estimated})^{(3)}$
		Data not available
		Expected low toxicity: $LC_{50} > 5 \text{ mg/l}$, 4h (estimated) ⁽³⁾
Skin Corrosion/Irritation		ed as a skin irritation. ⁽³⁾ Prolonged/repeated contact may cause
		which can lead to dermatitis.
Serious Eye		ed as an eye irritation. ⁽³⁾ Capable of slightly irritating.
Damage/Irritation		ed do an eye initation. Oupdole of olightly initating.
Respiratory or Skin	· No data available co	ncerning respiratory sensitisation.
Sensitisation	Not expected to be a	
Germ Cell Mutagenicity	: Not considered a mu	
Carcinogenicity		known to be associated with carcinogenic effects. ⁽³⁾
Reproductive Toxicity	: Not expected to be a	
Specific target organ toxicity	: Not expected to be a	Tiazaru. ⁽⁴⁾
Aspiration Hazard.	: If kinetic viscosity (@	$(40^{\circ}\text{C}) \leq 20.5 \text{mm}^{2/\text{s}}$, classified as an aspiration hazard category 1.
Aspiration nazaru.		(+0, 0) = 20.511112/3, classified as an aspiration flazard category 1.
12. ECOLOGICAL INFORMA		
Basis for Assessment		nave not been determined specifically for this product.
Dasis for Assessment		sed on a knowledge of the components and the ecotoxicology of
		s indicated otherwise, the data presented is representative of the
Caution		whole product, rather than for individual component(s).
		re. May cause physical fouling of aquatic organisms.
Toxicity		v toxicity: Practically non toxic: LC/LL/EL/IL50 >100mg/L ⁽³⁾
Mobility in soil	: Generally floats on w	
		onents have estimated log Koc >3, indicating these components
	-	bed onto soil and sediment and are not likely to leach to ground
.	water.	
Persistence/degradability		eadily biodegradable. Major constituents are expected to be
	inherently biodegrad	adie.

Nippon	Grease Co., Ltd. E4789006 Date: November 1, 2021 Page:4/5
Bioaccumulative Potential	: Not expected to be a hazard. It may contains components with the potential to bioaccumulate. ⁽³⁾
Hazardous to ozone layer	 Not classified because this product not contained substances listed on Montreal Protocol and Ozone Layer Protection Law.
13. DISPOSAL CONSIDERA	
Material Disposal	1 Waste disposal yourself or entrust the industrial waste treatment company who obtained the prefectural governor's permission or municipal corporation. Disposal should be in accordance with applicable regional, national, and local laws and regulations.
	2 Do not dispose into the environment, in drains or in water courses.
	3 For landfill disposal, destroy by fire and confirm cinders agreed to Waste Disposal 4 Law.
	In event of burning this material, ensure to carryout work in safe place with guards in position, and select a method that would not cause any harm or damage to others during combustion or explosion.
Container Disposal	: Purify and recycle or performs suitable disposal in accordance with the standard of related laws and regulations. Disposal with remove content completely.
14. TRANSPORT INFORMAT	ΓΙΟΝ
International Restriction UN Class, Shipping Name	: Not Dangerous Goods.
UN Number	: Not applicable.
Domestic Restriction	: Since domestic laws and regulations shown below are applicable, containers and transportation methods shall be required to follow each and every regulation.
Land Fire Service Law Container:	
Sea	: Ship Safety Law: Not Dangerous Goods.
Air Specific cofety measures	:Civil Aeronautics Act: Not Dangerous Goods. 1 Caution: Flammable.
Specific safety measures for transportation	2 Transport remarkably with containers may not cause friction or agitation.
·	3 Display signage on vehicle and provide with fire fighting equipment, if and when required to transport more than the specified quantity. Total piled height of vehicle shall be less than 3 meters.
	4 Consolidation of this material with dangerous goods belonging to the 1st and 6th Classification is prohibited.
	5 Abide by other laws and regulations that are applicable.
15. REGULATORY INFORM	ATION
Fire Service Law	: Dangerous goods. Group 4 (flammable liquid), Class 3 petroleum, Danger grade
Pollutant Release and Transfer Register (PRTR) Law	: Not applicable
Law Industrial Safety and Hea Law	Ith : Not applicable
Poisonous and Deleterio Substance Control Law	us : Not applicable
Marine Pollution Protecti	on : Waste Oil Regulation.
Sewage Control Law Water Pollution Preventio Law	: Mineral Oil Disposal Regulation. (5mg/L) : Oil Disposal Regulation. (5mg/L)
Waste Disposal and Publ Cleaning Law	ic : Industrial Waste Regulation.
16 OTHER INFORMATION	

16. OTHER INFORMATION

- Subscribe "%" in this document means weight percentage.

[Quotation]

- Recommendation of Occupational Exposure Limits (2018), Japanese Society of Occupational Health
 Thresholds limit values for chemical substances and physical agents and biological exposure indices, ACGIH (2012)
 SDS of EU suppliers (2010-2012)

[Reference]

Japanese Standards Association (JSA), JIS Z 7253:2019, JIS Z 7252:2019
National Institute of Technology and Evaluation (nite), "GHS Information"
Ministry of Economy, Trade and Industry, Chemical Management site.

- Ministry of Health, Labour and Welfare, "Label and SDS information for GHS model"

Safety Data Sheet (SDS) about hazardous chemical is provided for a entrepreneur as reference information for safety handling. Refer to this document and perform suitable handling. Nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use. There is no warranty against intellectual property infringement. The information contained in this document is based upon data believed to be reliable through our supply chain at the time. So, we could not guarantee all about the contents. This document is based on JIS Z7253:2019, and is not a guarantee of safety.

Contents of SDS updated periodically. SDS compliance is required as a rule to all business enterprises engaged in transaction of chemicals (including products containing them) with other businesses. Retailer/ Wholesaler must provide newest SDS to customers.